



HD MEDI  
Pharmaceutical Solutions

Just imagine...

new

# NS TYPE

JV-300NS10  
JV-360NS10  
JV-480NS10  
JV-576NS10



Model	JV-300NS10	JV-360NS10	JV-480NS10	JV-576NS10
Dimensions	WxD	967 x 870 <sub>mm</sub>	967 x 870 <sub>mm</sub>	1,262 x 1,020 <sub>mm</sub>
	H	1,996 <sub>mm</sub>	2,179 <sub>mm</sub>	1,996 <sub>mm</sub>
Canister capacity	300EA (S:120, L:120, L1:60)	360EA (S:120, L:180, L2:60)	480EA (S:192, L:192, L1:96)	576EA (S:192, L:288, L2:96)
Weight	About 600 <sub>kg</sub>	About 650 <sub>kg</sub>	About 750 <sub>kg</sub>	About 820 <sub>kg</sub>
Maximum working rate	Unit-dose : MAX, 65 per minute / Multi-dose : MAX, 50 per minute			
STS working rate	MAX, 55 per minute			
STS capacity	60 Pack (1 tray)			
Auto Canister working rate	MAX, 40 per minute			
Auto Canister capacity	MAX, 500 tablet (Based on 1 Tablet sized 7 <sub>mm</sub> )			
Equipable Auto Canister Quantity	MAX, 6EA (Optional)		MAX, 8EA (Optional)	
Pouch sizes (HxW)	70 x 55 <sub>mm</sub> / 70 x 75 <sub>mm</sub> / 70 x 82 <sub>mm</sub> (Optional)			
Tablet detection	Infrared light detection			
Display and input	Touch Screen 26.4 <sub>cm</sub> (10.4" ) / Able to Mount on Right, Left			
Power consumption / supply	300W (MAX, 620W) / 120V~, 60Hz, 220-240V~, 60Hz			
Operation Temperature / Humidity	0-40 <sup>o</sup> C / 10-80%			
Slide & STS	Automatic / Manual (Optional)			
Side Door	Glass door (Optional)			
Printing system	Thermal transfer system : Any number of type faces is possible			
Text info	Possible to support graphic windows environment, Possible to print all characters, icon and barcode,			

※ Product exterior and specifications are subject to change due to the company's research and development results without any prior notice.  
※ I-Relay is Optional

